

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 06.02.2020

Cement All

### **SECTION 1: Identification**

#### **Product identifier**

Product name: Rapid Set Cement Product code: 101002000, 101010050, 101010088, 101012000, 101013000

### Recommended use of the product and restriction on use

Relevant identified uses: Not determined or not applicable. Uses advised against: Not determined or not applicable. Reasons why uses advised against: Not determined or not applicable.

#### Manufacturer or supplier details

Manufacturer: United States CTS Cement Manufacturing Corporation 12442 Knott St. Garden Grove, CA 92841 800-929-3030 info@ctscement.com

### Emergency telephone number:

United States

CTS Cement Manufacturing Corporation 1-800-929-3030 (8 AM - 5 PM)

### SECTION 2: Hazard(s) identification

### GHS classification:

Skin irritation, category 2 Serious eye damage, category 1 Specific target organ toxicity - single exposure, category 3, respiratory irritation Carcinogenicity, category 1A Specific target organ toxicity - repeated exposure, category 2

Label elements

Hazard

pictograms:



Signal word: Danger

### Hazard statements:

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335 May cause respiratory irritation.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

Page 2 of 11

### Cement All

H350 May cause cancer.

H373 May cause damage to Lungs through prolonged or repeated exposure by inhalation.

### Precautionary statements:

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash hands/eyes/mouth/skin/clothing thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P233 Keep container tightly closed.

P281 Use personal protective equipment as required.

P321 Specific treatment (see supplemental first aid instructions on this label).

P362 Take off contaminated clothing and wash before reuse

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P332+P313 If skin irritation occurs: Get medical advice/attention

P310 Immediately call a POISON CENTER or doctor/physician.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P314 Get medical advice/attention if you feel unwell

P308+P313 If exposed or concerned: Get medical advice/attention

P306+P313 If exposed of concerned: Get med

P405 Store locked up.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazards not otherwise classified: None

### SECTION 3: Composition/information on ingredients

Identification	Name	Weight %
CAS number: 960375-09-1	Calcium sulfoaluminate cement	90-100
CAS number: 14808-60-7	Silica, crystalline quartz	<0.1

### Additional Information:

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of the OSHA Hazard Communication Standard (29 CFR §1910.1200).

### SECTION 4: First aid measures

### Description of first aid measures

General notes: Not determined or not applicable.

After inhalation:

### According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

#### Cement All

Loosen clothing as necessary and position individual in a comfortable position. Maintain an unobstructed airway. Get medical advice/attention if you feel unwell. Take precautions to ensure your own safety.

Remove source of exposure or move person to fresh

air.

Get medical advice if you feel unwell or concerned.

### After skin contact:

Rinse affected area with soap and water.

If symptoms develop or persist, seek medical attention.

Take off all contaminated clothing.

Gently blot or brush away excess product.

Wash with plenty of lukewarm, gently flowing water.

Get medical advice if skin irritation occurs or you feel unwell.

### After eye contact:

Rinse/flush exposed eye(s) gently using water for 15-20 minutes.

If symptoms develop or persist, seek medical attention.

Avoid direct contact and wear chemical protective gloves, if necessary.

Rinse eyes cautiously with lukewarm, gently flowing water for several minutes, while holding the eyelids open.

Remove contact lenses, if present and easy to do

so.

Continue rinsing until medical aid is available.

Immediately call a POISON CONTROL CENTER or seek medical attention.

### After swallowing:

Rinse mouth thoroughly. Seek medical attention if irritation, discomfort, or vomiting persists.

#### Most important symptoms and effects, both acute and delayed

#### Acute symptoms and effects:

Not determined or not applicable.

#### Delayed symptoms and effects:

Not determined or not applicable.

#### Immediate medical attention and special treatment

#### Specific treatment:

Not determined or not applicable.

#### Notes for the doctor:

Not determined or not applicable.

#### SECTION 5: Firefighting measures

#### Extinguishing media

#### Suitable extinguishing media:

Use appropriate fire suppression agents for adjacent combustible materials or sources of ignition.

### Unsuitable extinguishing media:

## Not determined or not applicable.

#### Specific hazards during fire-fighting:

Thermal decomposition can lead to release of irritating gases and vapors.

#### Special protective equipment for firefighters:

Use typical firefighting equipment, self-contained breathing apparatus, special tightly sealed suit.

### Special precautions:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

### Cement All

Carbon monoxide and carbon dioxide may form upon combustion Heating causes a rise in pressure, risk of bursting and combustion.

### SECTION 6: Accidental release measures

### Personal precautions, protective equipment and emergency procedures:

Ensure adequate ventilation. Ensure air handling systems are operational Wear protective eyewear, gloves, and clothing.

#### **Environmental precautions:**

Should not be released into the environment Prevent from reaching drains, sewer or waterway.

### Methods and material for containment and cleaning up:

Wear protective eyewear, gloves and clothing. Sweep or scoop up solid material while minimizing dust generation Dispose of contents / container in accordance with local regulations.

### Reference to other sections:

Not determined or not applicable.

### SECTION 7: Handling and storage

### Precautions for safe handling:

Use only with adequate ventilation. Avoid breathing dust. Do not eat, drink, smoke or use personal products when handling chemical substances.

### Conditions for safe storage, including any incompatibilities:

Keep container tightly sealed. Keep container dry. Store in a cool, well-ventilated area.

### SECTION 8: Exposure controls/personal protection

Only those substances with limit values have been included below.

#### Country (Legal Basis) Substance Identifier Permissible concentration ACGIH TLV TWA 0.025 mg/m<sup>3</sup> ACGIH Silica, crystalline quartz (Respirable) 14808-60-7 (Respirable fraction) TWA 0.025000 mg/m<sup>3</sup> USA. ACGIH 14808-60-7 Total Silica, crystalline quartz OSHA 8-hour TWA PEL: 0.025 United States (OSHA) Silica, crystalline quartz (Respirable) 14808-60-7 mg/m<sup>3</sup> (Respirable fraction, action level) Silica, crystalline quartz (Respirable) 14808-60-7 OSHA 8-hour TWA PEL: 0.05 mg/m<sup>3</sup> (Respirable fraction, exposure limit level) TWA 30.000000 mg/m 3 / Total Silica, crystalline quartz 14808-60-7 %SiO2+2 USA. OSHA

## Occupational Exposure limit values:

## According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

Cement All				
		Total Silica, crystalline quartz	14808-60-7	TWA 0.050000 mg/m <sup>3</sup> USA. NIOSH

Page 5 of 11

### According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Initial preparation date: 01.30.2019

### **Cement All**

Country (Legal Basis)	Substance	Identifier	Permissible concentration
NIOSH	Silica, crystalline quartz (Respirable)	14808-60-7	NIOSH TWA 0.05 mg/m <sup>3</sup>

### Biological limit values:

No biological exposure limits noted for the ingredient(s).

### Information on monitoring procedures:

Monitoring of the concentration of substances in the breathing zone of workers or in the general workplace may be required to confirm compliance with an OEL and adequacy of exposure controls. Biological monitoring may also be appropriate for some substances.

#### Appropriate engineering controls:

Emergency eyewash fountains and safety showers should be available in the immediate vicinity of use or handling.

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapor and mists below the applicable workplace exposure limits (Occupational Exposure Limits-OELs) indicated above.

### Personal protection equipment

### Eye and face protection:

Safety goggles or glasses, or appropriate eye protection.

### Skin and body protection:

Select glove material impermeable and resistant to the substance.

Wear appropriate clothing to prevent any possibility of skin contact.

#### **Respiratory protection:**

If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn.

#### General hygienic measures:

Avoid contact with skin, eyes and clothing. Wash hands before breaks and at the end of work. Wash contaminated clothing before reuse.

### SECTION 9: Physical and chemical properties

#### Information on basic physical and chemical properties

Appearance	Solid; tan powder
Odor	Low
Odor threshold	Not available
рН	11 - 12 when wet
Melting point/freezing point	Not available
Initial boiling point/range	Not applicable
Flash point (closed cup)	Not available
Evaporation rate	Not applicable
Flammability (solid, gas)	Not available
Upper flammability/explosive limit	Not available
Lower flammability/explosive limit	Not available
Vapor pressure	Not applicable
Vapor density	Not applicable

### According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

### Page 7 of 11

### Cement All

Density	Not available
Relative density	2.96 – 2.98 at 20°C
Solubilities	Partially soluble
Partition coefficient (n-octanol/water)	Not available
Auto/Self-ignition temperature	Not available
Decomposition temperature	2460°F (1350°C)
Dynamic viscosity	Not applicable
Kinematic viscosity	Not applicable
Explosive properties	Not available
Oxidizing properties	Not available

### Other information

Bulk density	60 lb/ft <sup>3</sup>
VOC (Weight %)	0 g/l when mixed with water

### SECTION 10: Stability and reactivity

### Reactivity:

Does not react under normal conditions of use and storage.

#### Chemical stability:

Stable under normal conditions of use and storage.

#### Possibility of hazardous reactions:

None under normal conditions of use and storage.

### Conditions to avoid:

None known.

#### Incompatible materials:

None known.

### Hazardous decomposition products:

None known.

### SECTION 11: Toxicological information

### Acute toxicity

Assessment: Based on available data, the classification criteria are not met. Product data: No data available. Substance data: No data available.

#### Skin corrosion/irritation

Assessment: Causes skin irritation Product data: No data available. Substance data:

### According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

### Initial preparation date: 01.30.2019

### Cement All

Name	Result
Calcium sulfoaluminate cement	Causes skin irritation.

### Serious eye damage/irritation

### Assessment:

Causes serious eye damage **Product data:** 

No data available.

#### Substance data:

Name	Result
Calcium sulfoaluminate cement	Causes serious eye damage.

### Respiratory or skin sensitization

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

#### Substance data:

No data available.

### Carcinogenicity

Assessment:

May cause cancer

Product data: No data available.

#### Substance data:

Name	Species	Result
Silica, crystalline quartz (Respirable)	Not applicable	Component may cause cancer.
Total Silica, crystalline quartz		1 - Group 1: Carcinogenic to humans (Quartz)

### International Agency for Research on Cancer (IARC):

Name	Classification
Silica, crystalline quartz (Respirable)	Group 1 - Carcinogenic to humans

### National Toxicology Program (NTP):

Name	Classification
Silica, crystalline quartz (Respirable)	Known to be human carcinogens

#### Germ cell mutagenicity

Assessment: Based on available data, the classification criteria are not met.

Product data:

No data available.

Substance data:

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

### **Cement All**

No data available.

### **Reproductive toxicity**

Assessment: Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data:

No data available.

### Specific target organ toxicity (single exposure)

#### Assessment:

May cause respiratory irritation

### Product data:

No data available.

#### Substance data:

Name	Result
Calcium sulfoaluminate cement	May cause respiratory irritation.

### Specific target organ toxicity (repeated exposure)

#### Assessment:

May cause damage to organs through prolonged or repeated exposure

#### Product data:

No data available.

#### Substance data:

Name	Result
Calcium sulfoaluminate cement	May cause damage to organs (Lungs) through prolonged or repeated exposure.
Silica, crystalline quartz	Component affects the lungs through repeated exposure.

#### Aspiration toxicity

Assessment: Based on available data, the classification criteria are not met.

#### Product data:

No data available.

Substance data: No data available.

Information on likely routes of exposure:

No data available.

Symptoms related to the physical, chemical and toxicological characteristics:

No data available.

Other information:

No data available.

### SECTION 12: Ecological information

#### Acute (short-term) toxicity

Assessment: Based on available data, the classification criteria are not met. Product data: No data available.

Substance data: No data available.

#### Chronic (long-term) toxicity

Assessment: Based on available data, the classification criteria are not met.

Product data: No data available.

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

### **Cement All**

Substance data: No data available.

### Persistence and degradability

Product data: No data available. Substance data: No data

available.

### **Bioaccumulative potential**

Product data: No data available.

Substance data: No data

available.

## Mobility in soil

Product data: No data available.

Substance data: No data available.

Other adverse effects: No data available.

### SECTION 13: Disposal considerations

### Disposal methods:

It is the responsibility of the waste generator to properly characterize all waste materials according to applicable regulatory entities.

### SECTION 14: Transport information

### United States Transportation of dangerous goods (49 CFR DOT)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Maritime Dangerous Goods (IMDG)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None
Packing group	None
Environmental hazards	None
Special precautions for user	None

### International Air Transport Association Dangerous Goods Regulations (IATA-DGR)

UN number	Not regulated
UN proper shipping name	Not regulated
UN transport hazard class(es)	None

### According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

### Cement All

Packing group	None
Environmental hazards	None
Special precautions for user	None

### SECTION 15: Regulatory information

### **United States regulations**

### Inventory listing (TSCA):

960375-09-1	Calcium sulfoaluminate cement	Listed
14808-60-7	Total Silica, crystalline quartz	Listed

Significant New Use Rule (TSCA Section 5): None of the ingredients are listed.

Export notification under TSCA Section 12(b): None of the ingredients are listed.

SARA Section 302 extremely hazardous substances: None of the ingredients are listed. None of the ingredients are listed.

SARA Section 313 toxic chemicals: None of the ingredients are listed.

**CERCLA:** None of the ingredients are listed.

**RCRA:** None of the ingredients are listed.

Section 112(r) of the Clean Air Act (CAA): None of the ingredients are listed.

### Massachusetts Right to Know:

960375-09-1	Calcium sulfoaluminate cement	Not Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Listed

### New Jersey Right to Know:

960375-09-1	Calcium sulfoaluminate cement	Not Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Listed

### New York Right to Know:

960375-09-1		Not Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Not Listed

### Pennsylvania Right to Know:

960375-09-1	Calcium sulfoaluminate cement	Not Listed
14808-60-7	Silica, crystalline quartz (Respirable)	Listed

### California Proposition 65:

▲ WARNING:

CANCER and REPRODUCTIVE HARM - www.P65Warnings.ca.gov

According to OSHA Hazard Communication Standard, 29 CFR 1910.1200

Initial preparation date: 01.30.2019

### Cement All

Page 12 of 11

### SECTION 16: Other information

#### Abbreviations and Acronyms: None

#### Disclaimer:

This product has been classified in accordance with OSHA HCS 2012 guidelines. The information provided in this SDS is correct, to the best of our knowledge, based on information available. The information given is designed only as a guidance for safe handling, use, storage, transportation and disposal and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials, unless specified in the text. The responsibility to provide a safe workplace remains with the user.

### NFPA: 3-0-0

### HMIS: 3-0-0

Initial preparation date: 06.02.2020

### End of Safety Data Sheet